

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	407.7 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	149.7V x 148.7H
	At 50% of Imax	100.0V x 98.9H
	At 90% of Imax	51.4V x 50.0H

Beam Flux	Total	1000.0 lumens per klm.
	To 10% of Imax	979.0 lumens per klm.
	To 50% of Imax	709.1 lumens per klm.
	To 90% of Imax	235.0 lumens per klm.

Upward LOR	0.0 %
Downward LOR	100.0 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2026-04-20

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:12.12V I:0.4462A P:3.481W PF:0.6439 Freq:59.97Hz Lamp Flux:59.7768x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Wall Light	WEIGHT:
SPEC.:3.5W RED	DIM.:	SERIAL No.:1
MFR.: Lumien Enterprise,Inc.	SUR.:	Shielding Angle:



DATA OF LAMP		Eff:17.17lm/W	
MODEL	W9A6-3.5W-BK	Imax (cd)	24.37
NOMINAL POWER (W)	3.5	AVAILABILITY (%)	97.9
RATED VOLTAGE (V)	12	Avai. FLUX (lm)	58.52
NOMINAL FLUX (lm)	59.7768	LOR (%)	100.0
LAMPS INSIDE	1	TOTAL FLUX (lm)	59.78
TEST VOLTAGE (V)	12	θ @50% (H,V)	99,100DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.07	0.00
90	0.00	0.00	0.00	0.01	0.03	0.04	0.06	0.07	0.07	0.08	0.07	0.07	0.06	0.04	0.02	0.01	0.00	0.00	0.63	0.31
80	0.00	0.00	0.01	0.04	0.07	0.10	0.13	0.15	0.17	0.18	0.17	0.15	0.13	0.09	0.05	0.02	0.00	0.00	1.47	1.38
70	0.00	0.00	0.02	0.06	0.12	0.18	0.22	0.26	0.29	0.30	0.28	0.26	0.21	0.14	0.08	0.03	0.01	0.00	2.47	2.42
60	0.00	0.01	0.03	0.08	0.16	0.25	0.32	0.38	0.42	0.43	0.41	0.37	0.30	0.20	0.11	0.05	0.01	0.00	3.55	3.52
50	0.00	0.01	0.04	0.11	0.20	0.32	0.42	0.50	0.55	0.56	0.54	0.48	0.38	0.25	0.14	0.06	0.02	0.00	4.58	4.56
40	0.00	0.01	0.05	0.13	0.24	0.37	0.50	0.59	0.64	0.66	0.63	0.57	0.44	0.30	0.17	0.07	0.02	0.00	5.39	5.37
30	0.00	0.02	0.06	0.14	0.26	0.40	0.54	0.65	0.69	0.71	0.69	0.62	0.48	0.33	0.18	0.08	0.02	0.00	5.88	5.86
20	0.00	0.02	0.06	0.15	0.28	0.42	0.56	0.66	0.71	0.72	0.70	0.63	0.50	0.34	0.19	0.08	0.02	0.00	6.05	6.04
10	0.00	0.02	0.06	0.15	0.27	0.42	0.56	0.66	0.71	0.72	0.71	0.64	0.50	0.35	0.19	0.08	0.02	0.00	6.06	6.04
0	0.00	0.01	0.06	0.14	0.26	0.40	0.54	0.65	0.69	0.71	0.69	0.62	0.48	0.33	0.18	0.08	0.02	0.00	5.87	5.86
-10	0.00	0.01	0.05	0.13	0.24	0.37	0.50	0.59	0.64	0.65	0.63	0.57	0.44	0.30	0.17	0.07	0.02	0.00	5.37	5.35
-20	0.00	0.01	0.04	0.11	0.20	0.31	0.42	0.49	0.54	0.55	0.53	0.48	0.37	0.25	0.14	0.06	0.02	0.00	4.53	4.51
-30	0.00	0.01	0.03	0.08	0.16	0.24	0.32	0.37	0.41	0.42	0.40	0.37	0.29	0.20	0.11	0.05	0.01	0.00	3.48	3.45
-40	0.00	0.00	0.02	0.06	0.11	0.17	0.22	0.25	0.28	0.28	0.27	0.25	0.20	0.14	0.08	0.03	0.01	0.00	2.38	2.34
-50	0.00	0.00	0.01	0.03	0.07	0.10	0.13	0.14	0.16	0.16	0.16	0.14	0.12	0.08	0.05	0.02	0.00	0.00	1.38	1.29
-60	0.00	0.00	0.00	0.01	0.03	0.04	0.05	0.06	0.06	0.07	0.06	0.06	0.05	0.04	0.02	0.01	0.00	0.00	0.56	0.22
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.05	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
Φ t	0.01	0.14	0.57	1.43	2.70	4.15	5.51	6.48	7.05	7.21	6.98	6.29	4.97	3.38	1.88	0.79	0.21	0.01	60	---
Φ a	0.00	0.03	0.48	1.35	2.62	4.08	5.44	6.41	6.97	7.14	6.91	6.22	4.91	3.32	1.82	0.72	0.11	0.00	---	59

one-half-peak spread: U:39.9,D:38.6 , L:41.5,R:29.9


NEMA Beam Type: Type 7

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2026-04-20

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.12V I:0.4462A P:3.481W PF:0.6439 Freq:59.97Hz Lamp Flux:59.7768x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Wall Light	WEIGHT:
SPEC.:3.5W RED	DIM.:	SERIAL No.:1
MFR.: Lumien Enterprise,Inc.	SUR.:	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2026-04-20

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.12V I:0.4462A P:3.481W PF:0.6439 Freq:59.97Hz Lamp Flux:59.7768x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Wall Light	WEIGHT:
SPEC.:3.5W RED	DIM.:	SERIAL No.:1
MFR.: Lumien Enterprise,Inc.	SUR.:	Shielding Angle:



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2026-04-20

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2026-04-20

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.12V I:0.4462A P:3.481W PF:0.6439 Freq:59.97Hz Lamp Flux:59.7768x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Wall Light	WEIGHT:
SPEC.:3.5W RED	DIM.:	SERIAL No.:1
MFR.: Lumien Enterprise,Inc.	SUR.:	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
 H(β) Interval: 0.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:ADMIN
 Test Date:2026-04-20

V(B) Range:-180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
 Humidity:65.0%
 Test Distance:13.563m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.12V I:0.4462A P:3.481W PF:0.6439 Freq:59.97Hz Lamp Flux:59.7768x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Wall Light	WEIGHT:
SPEC.:3.5W RED	DIM.:	SERIAL No.:1
MFR.: Lumien Enterprise,Inc.	SUR.:	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.02	0.01
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.14	0.30	0.43	0.54	0.64	0.73	0.76	0.78	0.84	0.90	0.91	0.91
-70	0.00	0.00	0.00	0.01	0.27	0.54	0.87	1.24	1.70	2.09	2.45	2.73	2.95	3.09	3.18	3.27	3.34	3.44	3.50
-60	0.00	0.00	0.00	0.36	0.80	1.34	1.93	2.60	3.35	4.15	4.80	5.41	5.82	6.15	6.43	6.64	6.88	7.08	7.19
-50	0.00	0.00	0.17	0.71	1.42	2.17	3.03	3.99	5.12	6.28	7.35	8.35	9.08	9.69	10.2	10.6	11.0	11.4	11.7
-40	0.00	0.00	0.37	1.10	1.97	2.95	4.05	5.36	6.91	8.43	9.87	11.2	12.5	13.4	14.2	14.8	15.3	15.9	16.2
-30	0.00	0.00	0.52	1.44	2.44	3.63	4.98	6.58	8.43	10.2	12.1	13.7	15.4	16.8	17.9	18.6	19.1	19.7	20.0
-20	0.00	0.00	0.65	1.66	2.82	4.13	5.69	7.56	9.75	11.5	13.6	15.5	17.4	19.1	20.5	21.4	21.8	22.3	22.6
-10	0.00	0.00	0.74	1.82	3.06	4.49	6.17	8.16	10.6	12.4	14.7	16.5	18.4	20.1	21.6	22.3	22.9	23.3	23.6
0	0.00	0.00	0.77	1.87	3.13	4.59	6.32	8.36	10.9	12.8	14.9	16.9	18.8	20.5	21.9	22.5	23.1	23.4	23.7
10	0.00	0.00	0.75	1.83	3.08	4.50	6.18	8.19	10.7	12.5	14.7	16.6	18.5	20.2	21.6	22.4	22.8	23.2	23.5
20	0.00	0.00	0.67	1.68	2.86	4.17	5.73	7.59	9.80	11.6	13.7	15.6	17.5	19.1	20.6	21.4	21.9	22.3	22.6
30	0.00	0.00	0.54	1.44	2.47	3.65	5.01	6.60	8.48	10.3	12.1	13.9	15.5	17.0	18.0	18.8	19.2	19.8	20.0
40	0.00	0.00	0.37	1.12	1.99	2.97	4.07	5.42	7.01	8.56	9.99	11.4	12.6	13.6	14.4	15.0	15.6	16.1	16.4
50	0.00	0.00	0.17	0.75	1.42	2.18	3.06	4.08	5.23	6.41	7.50	8.54	9.33	9.94	10.4	10.8	11.3	11.7	12.0
60	0.00	0.00	0.00	0.35	0.83	1.35	1.97	2.66	3.43	4.28	4.98	5.61	6.05	6.40	6.70	6.96	7.23	7.51	7.72
70	0.00	0.00	0.00	0.01	0.24	0.54	0.92	1.30	1.74	2.17	2.61	2.92	3.14	3.34	3.51	3.67	3.80	3.94	4.03
80	0.00	0.00	0.00	0.00	0.00	0.01	0.05	0.19	0.34	0.49	0.66	0.76	0.84	0.93	1.01	1.03	1.04	1.08	1.10
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.02	0.00

H(β) Range:-90 - 90DEG

H(β) Interval: 0.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:ADMIN

Test Date:2026-04-20

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352

Humidity:65.0%

Test Distance:13.563m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.12V I:0.4462A P:3.481W PF:0.6439 Freq:59.97Hz Lamp Flux:59.7768x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Wall Light	WEIGHT:
SPEC.:3.5W RED	DIM.:	SERIAL No.:1
MFR.: Lumien Enterprise,Inc.	SUR.:	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.95	0.97	0.96	0.96	0.96	0.94	0.89	0.81	0.69	0.57	0.39	0.23	0.10	0.03	0.00	0.00	0.00	0.00	
-70	3.53	3.53	3.56	3.55	3.55	3.48	3.35	3.12	2.76	2.30	1.79	1.33	0.93	0.57	0.23	0.01	0.00	0.00	
-60	7.23	7.20	7.16	7.11	7.00	6.77	6.45	5.86	5.20	4.38	3.51	2.69	1.95	1.29	0.71	0.20	0.00	0.00	
-50	11.6	11.5	11.4	11.4	11.1	10.6	9.89	8.97	7.84	6.62	5.38	4.12	3.02	2.07	1.20	0.49	0.01	0.00	
-40	16.2	16.1	16.0	15.9	15.4	14.6	13.4	12.0	10.5	8.77	7.13	5.48	4.04	2.80	1.67	0.77	0.05	0.00	
-30	20.2	20.1	20.1	20.0	19.2	18.1	16.6	14.7	12.8	10.7	8.77	6.74	4.92	3.42	2.11	0.99	0.12	0.00	
-20	22.8	22.8	22.9	22.6	21.9	20.5	18.8	16.8	14.6	12.2	10.0	7.74	5.63	3.92	2.46	1.18	0.19	0.00	
-10	23.9	23.8	24.1	23.6	23.1	21.7	20.0	18.0	15.9	13.2	10.8	8.41	6.10	4.25	2.68	1.30	0.23	0.00	
0	24.0	23.9	24.3	23.7	23.3	22.0	20.4	18.3	16.2	13.6	11.1	8.61	6.23	4.35	2.76	1.34	0.25	0.00	
10	23.9	23.9	24.0	23.4	22.9	21.6	19.8	17.9	15.7	13.2	10.8	8.37	6.08	4.25	2.68	1.30	0.24	0.00	
20	22.9	22.8	22.9	22.5	21.9	20.5	18.7	16.7	14.6	12.3	10.0	7.68	5.61	3.94	2.47	1.19	0.20	0.00	
30	20.3	20.2	20.2	20.0	19.4	18.2	16.7	14.8	12.9	10.8	8.81	6.75	4.94	3.44	2.14	1.01	0.13	0.00	
40	16.5	16.4	16.3	16.1	15.7	14.8	13.6	12.2	10.6	8.91	7.21	5.50	4.06	2.82	1.72	0.78	0.06	0.00	
50	12.0	12.0	11.8	11.7	11.4	10.9	10.1	9.16	8.00	6.76	5.46	4.17	3.03	2.07	1.22	0.52	0.02	0.00	
60	7.74	7.68	7.60	7.50	7.33	7.04	6.67	6.05	5.35	4.51	3.61	2.76	1.96	1.29	0.73	0.24	0.00	0.00	
70	4.05	4.03	4.03	3.98	3.88	3.75	3.57	3.28	2.89	2.43	1.90	1.40	0.97	0.56	0.25	0.03	0.00	0.00	
80	1.12	1.11	1.17	1.20	1.16	1.10	1.04	0.96	0.79	0.62	0.45	0.28	0.11	0.02	0.00	0.00	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

H(β) Range:-90 - 90DEG

H(β) Interval: 0.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:ADMIN

Test Date:2026-04-20

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352

Humidity:65.0%

Test Distance:13.563m [K=1.0000]

Remarks: