

Floodlight Summary:

Report based on lamp delivering 1000 lumens.


Maximum Intensity		2241.0 cd per klm.
(Luminaire orientation as tested.)		0.0 degrees vertical
		0.0 degrees horizontal
Beam Spread	At 10% of Imax	60.2V x 56.1H
	At 50% of Imax	38.1V x 39.6H
	At 90% of Imax	23.8V x 28.1H
Beam Flux	Total	1000.3 lumens per klm.
	To 10% of Imax	898.2 lumens per klm.
	To 50% of Imax	651.2 lumens per klm.
	To 90% of Imax	331.2 lumens per klm.
	Upward LOR	0.7 %
	Downward LOR	99.3 %
Luminaire Efficiency(Light Output Ratio)		100.0 %

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-06-07

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:12.18V I:1.292A P:11.39W PF:0.7240 Freq:59.97Hz Lamp Flux:64.7193x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Spotlight	RGBWWWEIGHT:
SPEC.:12W BLUE 40°LENS	DIM.:	SERIAL No.:2
MFR.: EVERFINE	SUR.:	Shielding Angle:DOWN-LIGHT SHROUD



DATA OF LAMP		Eff:5.68lm/W	
MODEL	D9A2-12W-BZ	Imax (cd)	145.0
NOMINAL POWER (W)	12	AVAILABILITY (%)	88.7
RATED VOLTAGE (V)	12	Avai. FLUX (lm)	57.40
NOMINAL FLUX (lm)	64.7193	LOR (%)	100.0
LAMPS INSIDE	1	TOTAL FLUX (lm)	64.72
TEST VOLTAGE (V)	12	θ @50% (H,V)	40,38DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.01	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.08	0.07	0.06	0.05	0.04	0.03	0.02	0.01	0.01	0.70	0.00
45	0.01	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.08	0.07	0.06	0.05	0.04	0.03	0.02	0.01	0.01	0.95	0.17
40	0.01	0.02	0.02	0.03	0.05	0.06	0.08	0.10	0.11	0.11	0.10	0.08	0.06	0.05	0.03	0.02	0.02	0.01	1.41	0.89
35	0.01	0.02	0.03	0.04	0.06	0.09	0.12	0.16	0.18	0.18	0.16	0.12	0.09	0.06	0.04	0.03	0.02	0.01	2.20	1.81
30	0.01	0.02	0.03	0.05	0.08	0.13	0.20	0.26	0.32	0.31	0.26	0.19	0.13	0.08	0.05	0.03	0.02	0.01	3.61	3.29
25	0.01	0.02	0.04	0.07	0.12	0.21	0.34	0.46	0.55	0.55	0.45	0.33	0.20	0.12	0.07	0.04	0.02	0.01	5.54	5.27
20	0.01	0.02	0.04	0.08	0.18	0.34	0.55	0.73	0.85	0.84	0.72	0.53	0.32	0.17	0.08	0.04	0.02	0.01	7.30	7.07
15	0.01	0.02	0.04	0.10	0.25	0.50	0.76	0.96	1.05	1.04	0.95	0.74	0.46	0.23	0.10	0.04	0.02	0.01	8.32	8.12
10	0.01	0.02	0.04	0.12	0.32	0.62	0.92	1.07	1.09	1.09	1.06	0.90	0.58	0.29	0.11	0.04	0.02	0.01	8.55	8.39
5	0.01	0.01	0.04	0.13	0.35	0.68	0.98	1.07	1.06	1.07	1.08	0.97	0.63	0.31	0.11	0.04	0.02	0.01	8.24	8.07
0	0.00	0.01	0.03	0.11	0.32	0.64	0.94	1.05	1.05	1.06	1.06	0.93	0.59	0.28	0.09	0.03	0.01	0.01	7.15	6.98
-5	0.00	0.01	0.02	0.08	0.24	0.50	0.78	0.96	1.02	1.03	0.96	0.77	0.46	0.21	0.07	0.02	0.01	0.00	4.96	4.76
-10	0.00	0.01	0.02	0.05	0.14	0.32	0.52	0.70	0.77	0.77	0.69	0.50	0.28	0.12	0.04	0.02	0.01	0.00	2.45	2.21
-15	0.00	0.01	0.01	0.02	0.06	0.15	0.26	0.36	0.39	0.39	0.34	0.24	0.13	0.05	0.02	0.01	0.01	0.00	0.80	0.39
-20	0.00	0.00	0.01	0.01	0.02	0.05	0.08	0.12	0.12	0.12	0.11	0.07	0.04	0.02	0.01	0.01	0.00	0.00	0.17	0.00
-25	0.00	0.00	0.00	0.01	0.01	0.01	0.02	0.02	0.01	0.01	0.02	0.02	0.01	0.01	0.01	0.00	0.00	0.00	0.06	0.00
-30	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.02	0.00
-35	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	---	---
-45	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	---	---
	-45	-40	-35	-30	-25	-20	-15	-10	HORIZONTAL (DEG)	10	15	20	25	30	35	40	45			
Φ t	0.10	0.20	0.40	0.95	2.26	4.36	6.62	8.09	8.66	8.65	8.03	6.44	4.05	2.04	0.87	0.40	0.21	0.11	62	---
Φ a	0.00	0.00	0.00	0.42	1.90	4.07	6.38	7.89	8.49	8.49	7.83	6.20	3.76	1.67	0.30	0.00	0.00	0.00	---	57

one-half-peak spread: U:9.3,D:14.0 , L:11.4,R:11.4


NEMA Beam Type: Type 4

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-06-07

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.18V I:1.292A P:11.39W PF:0.7240 Freq:59.97Hz Lamp Flux:64.7193x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Spotlight RGBWWEIGHT:	
SPEC.:12W BLUE 40°LENS	DIM.:	SERIAL No.:2
MFR.: EVERFINE	SUR.:	Shielding Angle:DOWN-LIGHT SHROUD




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-06-07

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.18V I:1.292A P:11.39W PF:0.7240 Freq:59.97Hz Lamp Flux:64.7193x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Spotlight RGBWWWEIGHT:	
SPEC.:12W BLUE 40°LENS	DIM.:	SERIAL No.:2
MFR.: EVERFINE	SUR.:	Shielding Angle:DOWN-LIGHT SHROUD



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-06-07

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-06-07

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.18V I:1.292A P:11.39W PF:0.7240 Freq:59.97Hz Lamp Flux:64.7193x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Spotlight RGBW	WEIGHT:
SPEC.:12W BLUE 40°LENS	DIM.:	SERIAL No.:2
MFR.: EVERFINE	SUR.:	Shielding Angle:DOWN-LIGHT SHROUD



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-06-07

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.18V I:1.292A P:11.39W PF:0.7240 Freq:59.97Hz Lamp Flux:64.7193x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Spotlight	RGBWWEIGHT:
SPEC.:12W BLUE 40°LENS	DIM.:	SERIAL No.:2
MFR.: EVERFINE	SUR.:	Shielding Angle:DOWN-LIGHT SHROUD

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.12	0.26	0.38	0.50	0.59	0.68	0.71
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.05	0.14	0.29	0.44	0.55	0.63	0.70	0.76
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.06	0.11	0.22	0.37	0.48	0.59	0.67	0.74
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.07	0.12	0.19	0.27	0.36	0.43	0.49
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.05	0.09	0.13	0.17	0.19
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.05	0.11	0.19	0.21	0.18	0.11	0.00
-30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.07	0.28	0.54	0.82	1.02	1.22	1.33	0.91	0.00
-20	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.44	0.98	1.68	3.54	8.04	15.5	25.7	30.2	27.0
-10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.27	0.92	1.95	5.00	16.0	40.6	73.0	105	121	121
0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.43	1.32	2.75	9.02	30.6	71.2	116	142	139	137
10	0.00	0.00	0.00	0.01	0.04	0.09	0.18	0.33	0.56	1.19	2.39	4.60	10.2	26.6	58.3	98.0	129	142	145
20	0.00	0.00	0.00	0.01	0.06	0.15	0.31	0.56	0.94	1.58	2.76	4.60	7.98	14.6	27.6	47.4	69.4	86.9	95.8
30	0.00	0.00	0.01	0.02	0.06	0.17	0.35	0.63	1.05	1.63	2.50	3.79	5.55	8.11	12.1	17.5	23.2	28.6	32.3
40	0.00	0.00	0.01	0.02	0.04	0.15	0.31	0.54	0.90	1.39	2.01	2.82	3.84	5.09	6.51	8.01	9.56	11.0	12.2
50	0.00	0.00	0.01	0.02	0.03	0.08	0.21	0.38	0.61	0.93	1.34	1.84	2.44	3.09	3.80	4.54	5.25	5.90	6.44
60	0.00	0.00	0.01	0.01	0.02	0.04	0.07	0.16	0.31	0.49	0.70	0.93	1.21	1.52	1.85	2.18	2.49	2.76	2.99
70	0.00	0.00	0.01	0.01	0.02	0.03	0.04	0.05	0.08	0.11	0.16	0.25	0.35	0.47	0.60	0.71	0.81	0.90	0.97
80	0.00	0.00	0.00	0.01	0.01	0.02	0.02	0.02	0.03	0.05	0.06	0.07	0.08	0.09	0.10	0.10	0.11	0.12	0.12
90	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.02
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.10	0.18	0.21	0.24	0.24
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.06	0.16	0.28	0.38	0.47	0.49	0.45
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.12	0.26	0.38	0.50	0.59	0.68	0.71

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-06-07

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.18V I:1.292A P:11.39W PF:0.7240 Freq:59.97Hz Lamp Flux:64.7193x1 lm																		
NAME: LED LANDSCAPE LIGHT									TYPE:Aluminum Spotlight RGBWEIGHT:									
SPEC.:12W BLUE 40°LENS									DIM.:					SERIAL No.:2				
MFR.: EVERFINE									SUR.:					Shielding Angle:DOWN-LIGHT SHROUD				

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.72	0.63	0.61	0.57	0.45	0.30	0.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-170	0.71	0.68	0.66	0.54	0.41	0.28	0.15	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-160	0.71	0.63	0.56	0.43	0.32	0.21	0.06	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-150	0.45	0.40	0.32	0.25	0.13	0.07	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-140	0.17	0.13	0.09	0.05	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-50	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-40	0.12	0.21	0.26	0.24	0.17	0.09	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-30	0.79	1.20	1.22	1.08	0.91	0.65	0.37	0.13	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-20	28.9	23.6	13.5	6.57	3.23	1.78	1.11	0.56	0.16	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-10	120	104	67.9	35.6	13.1	4.53	2.09	1.10	0.40	0.07	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
0	142	141	113	62.5	25.8	7.77	2.90	1.48	0.59	0.12	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
10	142	128	92.8	53.3	23.7	9.72	4.74	2.57	1.32	0.63	0.33	0.18	0.09	0.04	0.01	0.00	0.00	0.00	
20	85.5	67.3	45.3	26.1	14.3	8.07	4.72	2.88	1.66	0.96	0.56	0.31	0.15	0.06	0.01	0.00	0.00	0.00	
30	28.5	23.1	17.5	12.2	8.20	5.66	3.89	2.56	1.66	1.05	0.63	0.35	0.17	0.06	0.02	0.01	0.00	0.00	
40	11.0	9.59	8.06	6.57	5.15	3.89	2.85	2.01	1.39	0.90	0.54	0.31	0.15	0.04	0.02	0.01	0.00	0.00	
50	5.91	5.26	4.55	3.81	3.09	2.44	1.84	1.34	0.93	0.61	0.38	0.21	0.08	0.03	0.02	0.01	0.00	0.00	
60	2.76	2.49	2.18	1.85	1.52	1.21	0.93	0.70	0.49	0.31	0.16	0.07	0.04	0.02	0.01	0.01	0.00	0.00	
70	0.90	0.81	0.71	0.60	0.47	0.35	0.25	0.16	0.11	0.08	0.05	0.04	0.03	0.02	0.01	0.01	0.00	0.00	
80	0.12	0.11	0.10	0.10	0.09	0.08	0.07	0.06	0.05	0.03	0.02	0.02	0.02	0.01	0.01	0.00	0.00	0.00	
90	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
150	0.03	0.05	0.05	0.06	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
160	0.27	0.25	0.26	0.16	0.14	0.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
170	0.50	0.52	0.49	0.38	0.28	0.20	0.11	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
180	0.72	0.63	0.61	0.57	0.45	0.30	0.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

H(β) Range:-90 - 90DEG
 H(β) Interval: 0.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:ADMIN
 Test Date:2023-06-07

V(B) Range:-180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
 Humidity:65.0%
 Test Distance:13.563m [K=1.0000]
 Remarks: