

Floodlight Summary:

Report based on lamp delivering 1000 lumens.


Maximum Intensity		2311.9 cd per klm.
(Luminaire orientation as tested.)		0.0 degrees vertical
		0.0 degrees horizontal
Beam Spread	At 10% of Imax	63.0V x 60.8H
	At 50% of Imax	34.7V x 35.7H
	At 90% of Imax	13.7V x 13.1H
Beam Flux	Total	1000.3 lumens per klm.
	To 10% of Imax	886.2 lumens per klm.
	To 50% of Imax	489.4 lumens per klm.
	To 90% of Imax	97.8 lumens per klm.
	Upward LOR	0.8 %
	Downward LOR	99.2 %
Luminaire Efficiency(Light Output Ratio)		100.0 %

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:12.08V I:0.4354A P:3.515W PF:0.6681 Freq:59.99Hz Lamp Flux:93.1124x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 4110K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud



DATA OF LAMP		Eff:26.49lm/W	
MODEL	D1B1-A	Imax (cd)	215.3
NOMINAL POWER (W)	3.5	AVAILABILITY (%)	86.5
RATED VOLTAGE (V)	12	Avai. FLUX (lm)	80.50
NOMINAL FLUX (lm)	93.1124	LOR (%)	100.0
LAMPS INSIDE	1	TOTAL FLUX (lm)	93.11
TEST VOLTAGE (V)	12	θ @50% (H,V)	36,35DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.02	0.03	0.04	0.06	0.08	0.10	0.12	0.15	0.17	0.17	0.15	0.13	0.10	0.08	0.06	0.04	0.03	0.02	1.53	0.29
45	0.02	0.03	0.05	0.07	0.10	0.14	0.17	0.21	0.24	0.24	0.21	0.18	0.14	0.10	0.07	0.05	0.03	0.02	2.11	1.24
40	0.02	0.04	0.06	0.09	0.13	0.18	0.24	0.31	0.35	0.36	0.31	0.25	0.19	0.14	0.09	0.06	0.04	0.02	2.90	2.23
35	0.03	0.04	0.07	0.11	0.17	0.25	0.35	0.45	0.52	0.52	0.47	0.38	0.27	0.18	0.12	0.07	0.04	0.03	4.08	3.53
30	0.03	0.05	0.08	0.13	0.23	0.37	0.52	0.64	0.73	0.74	0.67	0.56	0.42	0.26	0.14	0.08	0.05	0.03	5.72	5.25
25	0.03	0.05	0.08	0.16	0.31	0.51	0.69	0.87	1.00	1.01	0.91	0.75	0.57	0.38	0.19	0.09	0.05	0.03	7.68	7.27
20	0.02	0.04	0.09	0.20	0.40	0.63	0.86	1.09	1.27	1.29	1.16	0.95	0.71	0.49	0.26	0.10	0.05	0.03	9.64	9.30
15	0.02	0.04	0.08	0.23	0.46	0.71	0.99	1.27	1.48	1.51	1.36	1.11	0.82	0.56	0.32	0.11	0.04	0.02	11.1	10.9
10	0.01	0.03	0.07	0.24	0.48	0.73	1.03	1.34	1.56	1.61	1.46	1.19	0.88	0.60	0.34	0.11	0.04	0.02	11.7	11.5
5	0.01	0.02	0.06	0.22	0.44	0.67	0.98	1.28	1.50	1.54	1.40	1.14	0.82	0.55	0.32	0.10	0.03	0.01	11.1	10.9
0	0.01	0.02	0.04	0.16	0.35	0.53	0.81	1.09	1.26	1.29	1.18	0.93	0.65	0.45	0.25	0.07	0.02	0.01	9.13	8.90
-5	0.01	0.01	0.03	0.10	0.24	0.37	0.52	0.75	0.89	0.91	0.82	0.61	0.45	0.32	0.16	0.05	0.02	0.01	6.26	6.01
-10	0.00	0.01	0.02	0.05	0.13	0.22	0.28	0.33	0.36	0.37	0.37	0.34	0.28	0.19	0.08	0.03	0.01	0.01	3.09	2.76
-15	0.00	0.01	0.01	0.02	0.05	0.10	0.13	0.14	0.11	0.12	0.16	0.18	0.15	0.08	0.03	0.02	0.01	0.00	1.32	0.47
-20	0.00	0.00	0.01	0.01	0.02	0.03	0.04	0.04	0.03	0.03	0.06	0.07	0.05	0.03	0.02	0.01	0.01	0.00	0.46	0.00
-25	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.00	0.01	0.02	0.02	0.01	0.01	0.01	0.01	0.00	0.00	0.14	0.00
-30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.06	0.00
-35	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.00
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-45	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-45 -40 -35 -30 -25 -20 -15 -10 HORIZONTAL (DEG) 10 15 20 25 30 35 40 45																				
Φ t	0.23	0.41	0.80	1.85	3.60	5.55	7.79	9.98	11.5	11.7	10.7	8.79	6.53	4.43	2.49	1.02	0.48	0.26	88	---
Φ a	0.00	0.00	0.00	1.10	3.11	5.17	7.48	9.74	11.3	11.5	10.5	8.47	6.17	3.97	1.86	0.15	0.00	0.00	---	80

one-half-peak spread: U:16.5,D:18.4 , L:17.5,R:18.5


NEMA Beam Type: Type 4

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.08V I:0.4354A P:3.515W PF:0.6681 Freq:59.99Hz Lamp Flux:93.1124x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 4110K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.08V I:0.4354A P:3.515W PF:0.6681 Freq:59.99Hz Lamp Flux:93.1124x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 4110K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.08V I:0.4354A P:3.515W PF:0.6681 Freq:59.99Hz Lamp Flux:93.1124x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 4110K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.08V I:0.4354A P:3.515W PF:0.6681 Freq:59.99Hz Lamp Flux:93.1124x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 4110K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.13	0.29	0.40	0.53	0.61	0.65	0.69	0.67
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.05	0.17	0.33	0.47	0.61	0.70	0.76	0.81	0.79
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.03	0.07	0.13	0.28	0.42	0.56	0.69	0.79	0.85	0.92
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.05	0.10	0.16	0.27	0.39	0.50	0.60	0.69	0.75
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.04	0.07	0.13	0.19	0.25	0.31	0.36	0.40
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.04	0.06	0.07	0.10	0.11
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.04	0.05	0.04	0.03	0.03	0.02	0.01	0.00
-50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.06	0.07	0.08	0.09	0.11	0.10	0.10	0.09	0.06	0.03	0.00
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.09	0.10	0.16	0.18	0.23	0.28	0.33	0.35	0.35	0.30	0.17	0.00
-30	0.00	0.00	0.00	0.00	0.00	0.01	0.10	0.12	0.20	0.27	0.40	0.57	0.90	1.33	1.83	2.33	2.58	1.80	0.00
-20	0.00	0.00	0.00	0.00	0.00	0.06	0.12	0.20	0.28	0.48	0.80	1.58	3.01	6.86	16.4	24.8	28.2	26.4	18.9
-10	0.00	0.00	0.00	0.00	0.00	0.10	0.14	0.26	0.41	0.74	1.54	3.39	9.72	30.7	52.0	73.3	111	139	145
0	0.00	0.00	0.00	0.00	0.00	0.12	0.15	0.28	0.47	0.93	2.09	5.01	17.9	52.0	82.9	116	157	192	211
10	0.00	0.01	0.01	0.03	0.09	0.31	0.53	0.94	1.56	2.70	4.88	9.08	19.5	47.1	77.5	109	143	173	191
20	0.00	0.01	0.03	0.06	0.15	0.42	0.80	1.36	2.19	3.61	5.88	9.82	16.2	27.9	48.5	71.5	90.9	107	117
30	0.00	0.01	0.04	0.08	0.18	0.43	0.90	1.47	2.35	3.58	5.48	8.22	12.3	17.9	25.1	34.1	44.0	52.6	58.6
40	0.00	0.02	0.05	0.09	0.18	0.37	0.77	1.34	2.04	3.02	4.27	5.99	8.21	10.9	14.2	17.9	21.7	25.1	27.8
50	0.00	0.02	0.05	0.09	0.16	0.29	0.52	0.93	1.52	2.19	2.99	3.95	5.10	6.38	7.81	9.32	10.8	12.1	13.2
60	0.00	0.02	0.05	0.09	0.14	0.22	0.33	0.52	0.78	1.17	1.68	2.26	2.85	3.51	4.13	4.78	5.40	5.96	6.42
70	0.00	0.02	0.05	0.08	0.13	0.17	0.24	0.31	0.40	0.51	0.66	0.84	1.04	1.26	1.50	1.75	1.98	2.18	2.35
80	0.00	0.02	0.04	0.07	0.10	0.14	0.17	0.21	0.26	0.30	0.35	0.39	0.44	0.49	0.55	0.61	0.66	0.71	0.76
90	0.00	0.02	0.04	0.05	0.07	0.09	0.11	0.13	0.14	0.16	0.18	0.20	0.22	0.24	0.25	0.27	0.29	0.31	0.33
100	0.00	0.02	0.03	0.04	0.05	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06
110	0.00	0.01	0.02	0.03	0.03	0.03	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.01	0.02	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.05	0.06	0.05	0.03	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.08	0.14	0.18	0.25	0.32	0.32	0.31
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.20	0.31	0.42	0.51	0.54	0.57	0.55
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.13	0.29	0.40	0.53	0.61	0.65	0.69	0.64

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.08V I:0.4354A P:3.515W PF:0.6681 Freq:59.99Hz Lamp Flux:93.1124x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 4110K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.77	0.76	0.75	0.65	0.58	0.41	0.23	0.08	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-170	0.84	0.82	0.79	0.70	0.57	0.40	0.22	0.08	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-160	0.87	0.83	0.76	0.62	0.48	0.32	0.19	0.07	0.03	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-150	0.70	0.62	0.53	0.42	0.30	0.18	0.10	0.05	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-140	0.37	0.32	0.25	0.19	0.13	0.07	0.04	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-130	0.10	0.07	0.06	0.04	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-60	0.02	0.04	0.05	0.07	0.07	0.07	0.07	0.06	0.03	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-50	0.05	0.09	0.12	0.14	0.15	0.16	0.16	0.15	0.13	0.11	0.06	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-40	0.27	0.46	0.55	0.51	0.47	0.40	0.31	0.26	0.23	0.19	0.15	0.09	0.01	0.00	0.00	0.00	0.00	0.00	
-30	3.20	4.57	3.79	2.74	2.02	1.39	0.84	0.56	0.37	0.29	0.22	0.16	0.07	0.00	0.00	0.00	0.00	0.00	
-20	29.4	33.5	31.9	25.5	12.1	4.51	2.41	1.17	0.68	0.42	0.30	0.23	0.13	0.01	0.00	0.00	0.00	0.00	
-10	145	124	87.6	64.7	43.6	17.2	5.02	2.37	1.07	0.56	0.37	0.26	0.17	0.04	0.00	0.00	0.00	0.00	
0	207	179	142	101	68.6	31.9	7.61	3.21	1.35	0.67	0.42	0.29	0.18	0.05	0.00	0.00	0.00	0.00	
10	180	155	123	90.2	59.9	27.0	10.7	5.72	3.03	1.71	1.05	0.66	0.37	0.13	0.03	0.01	0.01	0.00	
20	110	96.3	78.6	57.6	33.2	17.7	10.7	6.26	3.81	2.33	1.46	0.91	0.49	0.17	0.06	0.03	0.01	0.00	
30	54.0	45.9	35.5	26.0	18.5	12.8	8.48	5.64	3.68	2.43	1.58	0.96	0.49	0.18	0.08	0.04	0.01	0.00	
40	25.2	21.8	18.1	14.4	11.1	8.32	6.07	4.35	3.09	2.14	1.40	0.83	0.38	0.18	0.09	0.05	0.02	0.00	
50	12.1	10.8	9.35	7.85	6.43	5.15	4.02	3.06	2.25	1.56	0.97	0.53	0.29	0.16	0.09	0.05	0.02	0.00	
60	5.97	5.42	4.80	4.16	3.54	2.88	2.29	1.72	1.21	0.79	0.52	0.33	0.22	0.14	0.09	0.05	0.02	0.00	
70	2.19	1.99	1.75	1.50	1.26	1.04	0.84	0.66	0.51	0.40	0.31	0.24	0.17	0.13	0.08	0.05	0.02	0.00	
80	0.71	0.66	0.61	0.55	0.49	0.44	0.39	0.35	0.30	0.26	0.21	0.17	0.14	0.10	0.07	0.04	0.02	0.00	
90	0.31	0.29	0.27	0.25	0.24	0.22	0.20	0.18	0.16	0.14	0.13	0.11	0.09	0.07	0.05	0.04	0.02	0.00	
100	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.05	0.04	0.03	0.02	0.00	
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.03	0.03	0.03	0.02	0.01	0.00	
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.02	0.01	0.00	
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.00	
140	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00	
150	0.04	0.07	0.09	0.08	0.06	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00	
160	0.34	0.36	0.32	0.24	0.20	0.13	0.07	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
170	0.61	0.59	0.59	0.51	0.40	0.27	0.14	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
180	0.77	0.76	0.75	0.65	0.58	0.41	0.23	0.08	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks: