

Floodlight Summary:

Report based on lamp delivering 1000 lumens.


Maximum Intensity		2422.2 cd per klm.
(Luminaire orientation as tested.)		0.0 degrees vertical
		0.0 degrees horizontal
Beam Spread	At 10% of Imax	62.1V x 59.4H
	At 50% of Imax	34.8V x 34.3H
	At 90% of Imax	14.0V x 12.8H
Beam Flux	Total	1000.3 lumens per klm.
	To 10% of Imax	908.3 lumens per klm.
	To 50% of Imax	509.7 lumens per klm.
	To 90% of Imax	118.0 lumens per klm.
	Upward LOR	0.0 %
	Downward LOR	100.0 %
Luminaire Efficiency(Light Output Ratio)		100.0 %

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:12.11V I:0.3830A P:3.042W PF:0.6560 Freq:59.98Hz Lamp Flux:26.703x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 RED	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud



DATA OF LAMP		Eff:8.78lm/W	
MODEL	D1B1-A	Imax (cd)	64.68
NOMINAL POWER (W)	3.5	AVAILABILITY (%)	88.0
RATED VOLTAGE (V)	12	Avai. FLUX (lm)	23.49
NOMINAL FLUX (lm)	26.703	LOR (%)	100.0
LAMPS INSIDE	1	TOTAL FLUX (lm)	26.70
TEST VOLTAGE (V)	12	θ @50% (H,V)	34,35DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM															UNIT: lm			Φ t	Φ a
	0.00	0.01	0.01	0.02	0.02	0.03	0.04	0.04	0.05	0.05	0.04	0.04	0.03	0.02	0.02	0.01	0.01	0.00	0.43	0.07
45	0.01	0.01	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.07	0.06	0.05	0.04	0.03	0.02	0.01	0.01	0.01	0.61	0.35
40	0.01	0.01	0.02	0.03	0.04	0.05	0.07	0.09	0.10	0.11	0.09	0.08	0.06	0.04	0.03	0.02	0.01	0.01	0.85	0.66
35	0.01	0.01	0.02	0.03	0.05	0.07	0.10	0.13	0.15	0.16	0.15	0.12	0.09	0.06	0.04	0.02	0.01	0.01	1.21	1.05
30	0.01	0.01	0.02	0.04	0.06	0.10	0.14	0.18	0.22	0.23	0.21	0.18	0.14	0.09	0.05	0.03	0.01	0.01	1.71	1.57
25	0.01	0.01	0.02	0.04	0.08	0.13	0.19	0.25	0.29	0.31	0.28	0.24	0.19	0.13	0.07	0.03	0.01	0.01	2.28	2.16
20	0.01	0.01	0.02	0.04	0.09	0.16	0.23	0.31	0.37	0.39	0.36	0.30	0.23	0.17	0.10	0.04	0.02	0.01	2.85	2.74
15	0.00	0.01	0.02	0.05	0.10	0.17	0.26	0.35	0.43	0.45	0.43	0.36	0.27	0.19	0.12	0.04	0.01	0.01	3.28	3.20
10	0.00	0.01	0.01	0.04	0.10	0.17	0.26	0.36	0.44	0.48	0.46	0.40	0.30	0.21	0.13	0.05	0.01	0.00	3.44	3.37
5	0.00	0.00	0.01	0.03	0.09	0.15	0.24	0.34	0.42	0.46	0.44	0.38	0.28	0.19	0.12	0.04	0.01	0.00	3.23	3.17
0	0.00	0.00	0.01	0.02	0.07	0.12	0.20	0.29	0.35	0.38	0.37	0.30	0.22	0.16	0.10	0.03	0.01	0.00	2.63	2.57
-5	0.00	0.00	0.01	0.01	0.04	0.08	0.12	0.19	0.24	0.26	0.25	0.20	0.15	0.12	0.07	0.02	0.01	0.00	1.77	1.69
-10	0.00	0.00	0.00	0.01	0.02	0.04	0.06	0.08	0.09	0.10	0.11	0.11	0.10	0.07	0.03	0.01	0.00	0.00	0.85	0.74
-15	0.00	0.00	0.00	0.00	0.01	0.02	0.02	0.03	0.02	0.03	0.05	0.06	0.06	0.04	0.01	0.01	0.00	0.00	0.37	0.15
-20	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00	0.01	0.02	0.03	0.02	0.01	0.01	0.00	0.00	0.00	0.13	0.00
-25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.04	0.00
-30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00
-35	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-45	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-45 -40 -35 -30 -25 -20 -15 -10 HORIZONTAL (DEG) 10 15 20 25 30 35 40 45																				
Φ t	0.05	0.10	0.19	0.39	0.80	1.34	2.00	2.71	3.26	3.49	3.35	2.85	2.19	1.52	0.90	0.36	0.14	0.06	26	---
Φ a	0.00	0.00	0.00	0.12	0.64	1.22	1.91	2.64	3.20	3.42	3.26	2.75	2.08	1.39	0.73	0.13	0.00	0.00	---	23

one-half-peak spread: U:15.1,D:20.0 , L:17.2,R:17.4


NEMA Beam Type: Type 4

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.11V I:0.3830A P:3.042W PF:0.6560 Freq:59.98Hz Lamp Flux:26.703x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 RED	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.11V I:0.3830A P:3.042W PF:0.6560 Freq:59.98Hz Lamp Flux:26.703x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 RED	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.11V I:0.3830A P:3.042W PF:0.6560 Freq:59.98Hz Lamp Flux:26.703x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 RED	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.11V I:0.3830A P:3.042W PF:0.6560 Freq:59.98Hz Lamp Flux:26.703x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 RED	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.02	0.03	0.00	0.00
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.04	0.05	0.06	0.08
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.02
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.04	0.04	0.04	0.03	0.00
-30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.06	0.12	0.24	0.33	0.40	0.39	0.26	0.00
-20	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.10	0.26	0.54	1.05	2.45	4.60	6.10	6.20	4.72
-10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.22	0.61	1.48	5.02	10.7	16.6	28.1	37.5	40.6
0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.10	0.33	0.90	2.57	9.38	18.1	27.5	40.1	52.1	61.6
10	0.00	0.00	0.00	0.00	0.02	0.05	0.10	0.18	0.32	0.60	1.19	2.30	4.40	9.97	18.5	28.0	38.7	49.2	56.3
20	0.00	0.00	0.00	0.01	0.03	0.09	0.18	0.31	0.53	0.89	1.57	2.66	4.46	7.31	12.2	18.9	25.4	31.1	35.0
30	0.00	0.00	0.00	0.01	0.03	0.09	0.20	0.35	0.58	0.92	1.43	2.25	3.42	5.08	7.23	9.82	12.7	15.5	17.6
40	0.00	0.00	0.00	0.01	0.03	0.07	0.17	0.31	0.50	0.76	1.12	1.60	2.24	3.04	4.04	5.13	6.23	7.25	8.06
50	0.00	0.00	0.00	0.00	0.02	0.05	0.10	0.21	0.36	0.54	0.76	1.02	1.34	1.72	2.12	2.56	2.98	3.38	3.70
60	0.00	0.00	0.00	0.00	0.01	0.02	0.05	0.09	0.15	0.26	0.39	0.54	0.70	0.87	1.05	1.23	1.40	1.55	1.67
70	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.04	0.06	0.10	0.14	0.19	0.25	0.29	0.35	0.42	0.47	0.51
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.02	0.03	0.03	0.04	0.04
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2025-07-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.11V I:0.3830A P:3.042W PF:0.6560 Freq:59.98Hz Lamp Flux:26.703x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Spot Light Non LED	WEIGHT:
SPEC.:3.5W MR16 RED	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:Uplight Shroud

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-170	0.00	0.03	0.02	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-160	0.06	0.05	0.04	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-150	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-40	0.08	0.13	0.14	0.11	0.07	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-30	1.33	2.00	1.71	1.08	0.68	0.38	0.15	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-20	8.89	11.0	11.1	9.59	5.32	1.78	0.75	0.24	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-10	43.5	38.8	29.0	22.3	16.2	7.54	1.91	0.66	0.16	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
0	64.6	59.6	48.5	35.4	24.6	13.1	3.09	0.99	0.23	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
10	55.2	49.3	40.4	30.2	21.1	10.5	3.60	1.63	0.72	0.32	0.18	0.10	0.05	0.02	0.00	0.00	0.00	0.00	
20	33.8	30.3	25.3	19.3	11.6	5.70	3.15	1.71	0.93	0.53	0.31	0.18	0.09	0.03	0.01	0.00	0.00	0.00	
30	16.6	14.3	11.1	7.98	5.52	3.68	2.34	1.47	0.92	0.58	0.35	0.20	0.09	0.03	0.01	0.00	0.00	0.00	
40	7.31	6.31	5.23	4.11	3.09	2.26	1.60	1.12	0.76	0.50	0.31	0.17	0.07	0.03	0.01	0.00	0.00	0.00	
50	3.38	2.98	2.56	2.12	1.72	1.34	1.02	0.76	0.54	0.36	0.21	0.10	0.05	0.02	0.00	0.00	0.00	0.00	
60	1.55	1.40	1.23	1.05	0.87	0.70	0.54	0.39	0.26	0.15	0.09	0.05	0.02	0.01	0.00	0.00	0.00	0.00	
70	0.47	0.42	0.35	0.29	0.25	0.19	0.14	0.10	0.06	0.04	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
80	0.04	0.03	0.03	0.02	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

H(β) Range:-90 - 90DEG
 H(β) Interval: 0.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:ADMIN
 Test Date:2025-07-25

V(B) Range:-180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
 Humidity:65.0%
 Test Distance:13.563m [K=1.0000]
 Remarks: