

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	373.3 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	157.6V x 153.9H
	At 50% of Imax	109.4V x 108.5H
	At 90% of Imax	45.9V x 45.6H

Beam Flux	Total	1000.0 lumens per klm.
	To 10% of Imax	986.4 lumens per klm.
	To 50% of Imax	727.1 lumens per klm.
	To 90% of Imax	173.7 lumens per klm.

Upward LOR	0.0 %
Downward LOR	100.0 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-04-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:12.14V I:0.4128A P:2.393W PF:0.4776 Freq:59.97Hz Lamp Flux:46.5348x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light RGBWW WEIGHT:	
SPEC.:2.5W 2700K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



DATA OF LAMP		Eff:19.44lm/W	
MODEL	W9B4-2.5W-A	Imax (cd)	17.37
NOMINAL POWER(W)	2.5	AVAILABILITY(%)	98.6
RATED VOLTAGE (V)	12	Avai. FLUX(lm)	45.89
NOMINAL FLUX(lm)	46.5348	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	46.53
TEST VOLTAGE (V)	12	θ @50% (H,V)	108,109DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.02	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.10	0.00
90	0.00	0.00	0.01	0.02	0.04	0.06	0.07	0.08	0.09	0.09	0.08	0.06	0.04	0.02	0.01	0.00	0.00	0.00	0.67	0.53
80	0.00	0.00	0.02	0.05	0.08	0.12	0.14	0.17	0.18	0.17	0.16	0.13	0.10	0.06	0.03	0.01	0.00	0.00	1.43	1.39
70	0.00	0.01	0.04	0.08	0.12	0.17	0.22	0.25	0.26	0.26	0.24	0.20	0.15	0.10	0.06	0.02	0.00	0.00	2.19	2.17
60	0.00	0.01	0.05	0.10	0.16	0.23	0.28	0.32	0.34	0.34	0.31	0.26	0.21	0.14	0.08	0.03	0.01	0.00	2.88	2.87
50	0.00	0.02	0.06	0.12	0.20	0.27	0.34	0.38	0.41	0.40	0.37	0.32	0.25	0.17	0.10	0.04	0.01	0.00	3.49	3.48
40	0.00	0.02	0.07	0.14	0.23	0.31	0.38	0.43	0.46	0.46	0.43	0.36	0.28	0.20	0.12	0.05	0.01	0.00	3.97	3.96
30	0.00	0.02	0.08	0.16	0.24	0.33	0.41	0.47	0.50	0.50	0.46	0.40	0.31	0.22	0.13	0.06	0.01	0.00	4.30	4.29
	0.00	0.03	0.08	0.16	0.25	0.35	0.43	0.49	0.52	0.52	0.48	0.41	0.32	0.22	0.13	0.06	0.01	0.00	4.47	4.46
	0.00	0.03	0.08	0.16	0.25	0.35	0.43	0.49	0.52	0.51	0.48	0.41	0.32	0.22	0.13	0.06	0.01	0.00	4.46	4.45
	0.00	0.02	0.08	0.15	0.24	0.33	0.41	0.47	0.50	0.49	0.46	0.39	0.31	0.21	0.13	0.06	0.01	0.00	4.27	4.27
-30	0.00	0.02	0.07	0.14	0.22	0.31	0.38	0.43	0.46	0.45	0.42	0.36	0.28	0.20	0.12	0.05	0.01	0.00	3.92	3.92
-40	0.00	0.02	0.06	0.12	0.20	0.27	0.33	0.38	0.40	0.40	0.37	0.32	0.25	0.17	0.10	0.04	0.01	0.00	3.43	3.42
-50	0.00	0.01	0.05	0.10	0.16	0.22	0.28	0.31	0.33	0.33	0.30	0.26	0.20	0.14	0.08	0.03	0.00	0.00	2.82	2.81
-60	0.00	0.01	0.04	0.07	0.12	0.17	0.21	0.24	0.25	0.25	0.23	0.19	0.15	0.10	0.06	0.02	0.00	0.00	2.12	2.10
-70	0.00	0.00	0.02	0.05	0.08	0.11	0.14	0.16	0.17	0.17	0.15	0.13	0.09	0.06	0.03	0.01	0.00	0.00	1.36	1.32
-80	0.00	0.00	0.01	0.02	0.03	0.05	0.07	0.08	0.08	0.08	0.07	0.05	0.04	0.02	0.01	0.00	0.00	0.00	0.59	0.44
-90	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.06	0.00
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
Φ t	0.01	0.24	0.81	1.66	2.65	3.65	4.53	5.18	5.50	5.44	5.02	4.27	3.31	2.28	1.32	0.56	0.11	0.00	47	---
Φ a	0.00	0.20	0.77	1.62	2.62	3.62	4.49	5.14	5.46	5.41	4.98	4.23	3.27	2.24	1.28	0.52	0.05	0.00	---	46

one-half-peak spread: U:54.9,D:52.6 , L:44.6,R:36.4


NEMA Beam Type: Type 7

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-04-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.14V I:0.4128A P:2.393W PF:0.4776 Freq:59.97Hz Lamp Flux:46.5348x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light RGBWW WEIGHT:	
SPEC.:2.5W 2700K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-04-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.14V I:0.4128A P:2.393W PF:0.4776 Freq:59.97Hz Lamp Flux:46.5348x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light RGBWW WEIGHT:	
SPEC.:2.5W 2700K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-04-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-04-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.14V I:0.4128A P:2.393W PF:0.4776 Freq:59.97Hz Lamp Flux:46.5348x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light RGBWW	WEIGHT:
SPEC.:2.5W 2700K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-04-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.14V I:0.4128A P:2.393W PF:0.4776 Freq:59.97Hz Lamp Flux:46.5348x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light RGBWW	WEIGHT:
SPEC.:2.5W 2700K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.03	0.13	0.31	0.48	0.64	0.77	0.89	1.01	1.10	1.17	1.22	1.25	1.25	1.24
-70	0.00	0.00	0.00	0.16	0.59	1.01	1.45	1.84	2.23	2.60	2.90	3.22	3.47	3.68	3.86	3.99	4.07	4.11	4.09
-60	0.00	0.00	0.14	0.80	1.49	2.15	2.82	3.47	4.07	4.64	5.15	5.61	6.01	6.36	6.62	6.82	6.95	7.00	6.98
-50	0.00	0.00	0.52	1.43	2.33	3.26	4.15	5.01	5.82	6.60	7.32	7.94	8.44	8.88	9.22	9.50	9.67	9.75	9.74
-40	0.00	0.00	0.87	1.98	3.09	4.24	5.34	6.41	7.46	8.38	9.18	9.94	10.6	11.1	11.5	11.9	12.1	12.2	12.2
-30	0.00	0.05	1.17	2.45	3.76	5.07	6.35	7.65	8.76	9.81	10.7	11.6	12.3	12.9	13.5	13.9	14.1	14.2	14.2
-20	0.00	0.10	1.40	2.83	4.26	5.69	7.16	8.53	9.72	10.9	11.9	12.9	13.7	14.4	15.0	15.3	15.7	15.9	15.9
-10	0.00	0.13	1.55	3.01	4.57	6.10	7.69	9.08	10.4	11.6	12.7	13.6	14.6	15.3	15.9	16.4	16.7	16.9	16.8
0	0.00	0.14	1.61	3.09	4.70	6.26	7.93	9.31	10.7	11.9	13.1	14.1	15.0	15.6	16.5	16.8	17.2	17.4	17.3
10	0.00	0.13	1.56	3.02	4.59	6.11	7.71	9.11	10.5	11.6	12.7	13.7	14.6	15.3	16.0	16.5	16.8	17.0	17.0
20	0.00	0.10	1.41	2.85	4.29	5.72	7.21	8.58	9.78	11.0	12.0	13.0	13.8	14.5	15.1	15.5	15.8	16.0	16.0
30	0.00	0.05	1.18	2.48	3.80	5.11	6.41	7.72	8.85	9.91	10.9	11.7	12.5	13.1	13.6	14.0	14.3	14.5	14.5
40	0.00	0.01	0.89	2.01	3.14	4.31	5.41	6.51	7.57	8.50	9.31	10.1	10.7	11.3	11.7	12.1	12.3	12.5	12.5
50	0.00	0.00	0.54	1.47	2.39	3.34	4.24	5.11	5.94	6.74	7.48	8.11	8.64	9.09	9.45	9.75	9.94	10.0	10.0
60	0.00	0.00	0.16	0.84	1.55	2.23	2.92	3.59	4.21	4.79	5.32	5.80	6.23	6.59	6.89	7.10	7.25	7.33	7.33
70	0.00	0.00	0.01	0.20	0.65	1.09	1.55	1.96	2.37	2.76	3.09	3.43	3.69	3.93	4.12	4.27	4.37	4.42	4.42
80	0.00	0.00	0.00	0.00	0.02	0.08	0.22	0.41	0.60	0.77	0.93	1.08	1.21	1.32	1.41	1.49	1.54	1.57	1.58
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-04-25

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.14V I:0.4128A P:2.393W PF:0.4776 Freq:59.97Hz Lamp Flux:46.5348x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light RGBWW	WEIGHT:
SPEC.:2.5W 2700K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	1.17	1.09	0.99	0.87	0.74	0.61	0.48	0.38	0.28	0.18	0.10	0.04	0.01	0.00	0.00	0.00	0.00	0.00	
-70	4.01	3.88	3.71	3.48	3.22	2.91	2.57	2.19	1.77	1.35	0.90	0.48	0.22	0.10	0.02	0.00	0.00	0.00	
-60	6.89	6.72	6.49	6.19	5.84	5.40	4.93	4.38	3.77	3.12	2.43	1.72	1.00	0.35	0.09	0.01	0.00	0.00	
-50	9.63	9.42	9.12	8.74	8.29	7.71	7.11	6.38	5.63	4.81	3.92	2.98	2.03	1.07	0.24	0.04	0.00	0.00	
-40	12.1	11.8	11.5	11.1	10.5	9.81	9.03	8.20	7.25	6.25	5.22	4.11	2.94	1.77	0.64	0.05	0.00	0.00	
-30	14.1	13.9	13.5	13.0	12.4	11.6	10.7	9.68	8.58	7.42	6.24	5.01	3.70	2.36	1.04	0.05	0.00	0.00	
-20	15.8	15.5	15.1	14.5	13.7	12.9	11.9	10.8	9.62	8.32	7.02	5.67	4.27	2.79	1.33	0.11	0.00	0.00	
-10	16.8	16.5	16.1	15.4	14.7	13.7	12.7	11.5	10.2	8.88	7.46	6.03	4.58	3.05	1.52	0.17	0.00	0.00	
0	17.1	16.9	16.4	15.7	14.9	14.0	12.9	11.7	10.4	9.04	7.63	6.11	4.64	3.11	1.56	0.18	0.00	0.00	
10	16.9	16.6	16.1	15.5	14.8	13.8	12.7	11.5	10.2	8.91	7.49	6.06	4.60	3.06	1.53	0.18	0.00	0.00	
20	15.9	15.6	15.2	14.6	13.9	13.0	12.0	10.9	9.68	8.38	7.07	5.72	4.30	2.82	1.35	0.12	0.01	0.00	
30	14.4	14.1	13.7	13.2	12.5	11.7	10.8	9.79	8.68	7.51	6.32	5.08	3.75	2.40	1.07	0.07	0.01	0.00	
40	12.3	12.1	11.7	11.3	10.7	9.98	9.18	8.33	7.37	6.36	5.31	4.18	3.01	1.83	0.67	0.07	0.01	0.00	
50	9.91	9.69	9.38	8.97	8.50	7.91	7.28	6.55	5.77	4.94	4.02	3.07	2.10	1.12	0.28	0.06	0.00	0.00	
60	7.22	7.03	6.77	6.46	6.07	5.63	5.12	4.54	3.92	3.26	2.55	1.82	1.08	0.42	0.13	0.04	0.00	0.00	
70	4.32	4.18	3.99	3.75	3.47	3.14	2.78	2.38	1.93	1.48	1.02	0.59	0.30	0.16	0.06	0.01	0.00	0.00	
80	1.49	1.38	1.25	1.11	0.95	0.81	0.67	0.53	0.41	0.30	0.21	0.13	0.06	0.02	0.00	0.00	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

H(β) Range:-90 - 90DEG
 H(β) Interval: 0.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:ADMIN
 Test Date:2023-04-25

V(B) Range:-180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
 Humidity:65.0%
 Test Distance:13.563m [K=1.0000]
 Remarks: