

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	699.8 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	101.6V x 118.5H
	At 50% of Imax	70.5V x 79.4H
	At 90% of Imax	35.8V x 44.6H

Beam Flux	Total	1000.1 lumens per klm.
	To 10% of Imax	936.8 lumens per klm.
	To 50% of Imax	699.2 lumens per klm.
	To 90% of Imax	216.4 lumens per klm.

Upward LOR	0.5 %
Downward LOR	99.6 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-13

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:12.06V I:0.2564A P:1.897W PF:0.6133 Freq:59.97Hz Lamp Flux:94.6795x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light	WEIGHT:
SPEC.:2.5W 3000K Transparent lattice glass	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



DATA OF LAMP		Eff:49.92lm/W	
MODEL	W3B2-2.5W-30K-A	Imax (cd)	66.26
NOMINAL POWER (W)	2.5	AVAILABILITY (%)	93.0
RATED VOLTAGE (V)	12	Avai. FLUX (lm)	88.08
NOMINAL FLUX (lm)	94.6795	LOR (%)	100.0
LAMPS INSIDE	1	TOTAL FLUX (lm)	94.68
TEST VOLTAGE (V)	12	θ @50% (H,V)	79,71DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.02	0.02	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.11	0.00
90	0.00	0.00	0.00	0.01	0.02	0.04	0.05	0.06	0.08	0.08	0.06	0.05	0.04	0.02	0.01	0.00	0.00	0.00	0.52	0.00
80	0.00	0.00	0.01	0.03	0.05	0.08	0.12	0.14	0.16	0.16	0.14	0.11	0.08	0.05	0.03	0.01	0.00	0.00	1.18	0.06
70	0.00	0.00	0.02	0.05	0.09	0.15	0.21	0.28	0.32	0.31	0.27	0.21	0.14	0.09	0.04	0.02	0.00	0.00	2.20	1.57
60	0.00	0.00	0.03	0.07	0.15	0.26	0.42	0.60	0.73	0.72	0.59	0.41	0.25	0.14	0.07	0.02	0.00	0.00	4.45	4.11
50	0.00	0.01	0.03	0.10	0.22	0.46	0.83	1.20	1.44	1.43	1.17	0.79	0.43	0.21	0.09	0.03	0.01	0.00	8.45	8.21
40	0.00	0.01	0.04	0.13	0.32	0.73	1.25	1.66	1.85	1.84	1.63	1.20	0.68	0.30	0.12	0.04	0.01	0.00	11.8	11.6
30	0.00	0.01	0.05	0.16	0.42	0.94	1.47	1.77	1.94	1.94	1.76	1.42	0.88	0.39	0.14	0.05	0.01	0.00	13.3	13.2
20	0.00	0.01	0.05	0.17	0.48	1.02	1.52	1.78	1.92	1.92	1.78	1.47	0.95	0.43	0.15	0.05	0.01	0.00	13.7	13.6
10	0.00	0.01	0.05	0.17	0.46	0.96	1.45	1.71	1.82	1.83	1.71	1.40	0.89	0.41	0.15	0.05	0.01	0.00	13.0	12.9
0	0.00	0.01	0.04	0.14	0.36	0.76	1.22	1.54	1.66	1.66	1.53	1.18	0.69	0.32	0.12	0.04	0.01	0.00	11.3	11.1
-10	0.00	0.01	0.04	0.10	0.24	0.50	0.80	1.14	1.28	1.27	1.11	0.76	0.45	0.22	0.09	0.03	0.01	0.00	8.05	7.82
-20	0.00	0.00	0.03	0.07	0.15	0.27	0.42	0.50	0.51	0.50	0.47	0.38	0.25	0.13	0.06	0.02	0.00	0.00	3.77	3.42
-30	0.00	0.00	0.02	0.04	0.08	0.13	0.17	0.19	0.15	0.14	0.18	0.16	0.12	0.07	0.04	0.02	0.00	0.00	1.51	0.49
-40	0.00	0.00	0.01	0.02	0.04	0.06	0.07	0.06	0.03	0.03	0.05	0.06	0.05	0.04	0.02	0.01	0.00	0.00	0.55	0.00
-50	0.00	0.00	0.00	0.01	0.02	0.02	0.03	0.02	0.01	0.01	0.02	0.02	0.02	0.02	0.01	0.00	0.00	0.00	0.21	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.05	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90 -80 -70 -60 -50 -40 -30 -20 HORIZONTAL (DEG) 20 30 40 50 60 70 80 90																				
Φ t	0.00	0.08	0.42	1.27	3.12	6.40	10.0	12.6	13.9	13.9	12.5	9.64	5.93	2.84	1.15	0.39	0.08	0.00	94	---
Φ a	0.00	0.00	0.00	0.72	2.68	5.99	9.62	12.3	13.5	13.5	12.1	9.23	5.50	2.37	0.55	0.00	0.00	0.00	---	88

one-half-peak spread: U:43.3,D:16.4 , L:36.8,R:32.9


NEMA Beam Type: Type 6

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-13

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.06V I:0.2564A P:1.897W PF:0.6133 Freq:59.97Hz Lamp Flux:94.6795x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light	WEIGHT:
SPEC.:2.5W 3000K Transparent lattice glass	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-13

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.06V I:0.2564A P:1.897W PF:0.6133 Freq:59.97Hz Lamp Flux:94.6795x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light	WEIGHT:
SPEC.:2.5W 3000K Transparent lattice glass	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-13

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-13

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.06V I:0.2564A P:1.897W PF:0.6133 Freq:59.97Hz Lamp Flux:94.6795x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light	WEIGHT:
SPEC.:2.5W 3000K Transparent lattice glass	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-13

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.06V I:0.2564A P:1.897W PF:0.6133 Freq:59.97Hz Lamp Flux:94.6795x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light	WEIGHT:
SPEC.:2.5W 3000K Transparent lattice glass	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.07	0.11	0.17	0.24	0.28	0.35	0.41	0.45	0.44
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.09	0.14	0.20	0.26	0.30	0.37	0.41	0.44
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.03	0.07	0.13	0.19	0.24	0.29	0.34	0.37	0.41
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.05	0.09	0.15	0.20	0.24	0.29	0.32	0.34	0.36
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.04	0.08	0.11	0.15	0.19	0.23	0.25	0.27
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.03	0.05	0.07	0.09	0.10	0.11
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.03	0.04	0.05	0.05	0.04	0.03	0.02	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.07	0.19	0.30	0.40	0.47	0.52	0.55	0.53	0.50	0.45	0.36	0.26	0.13	0.00
-60	0.00	0.00	0.00	0.02	0.22	0.46	0.69	0.92	1.13	1.35	1.49	1.56	1.57	1.47	1.31	1.07	0.76	0.39	0.00
-50	0.00	0.00	0.00	0.21	0.58	0.97	1.39	1.90	2.35	2.76	3.13	3.44	3.56	3.73	3.76	3.50	2.99	2.27	1.37
-40	0.00	0.00	0.03	0.44	0.95	1.57	2.36	3.18	4.05	5.06	6.24	7.53	8.63	9.71	10.6	10.7	10.0	8.56	6.52
-30	0.00	0.00	0.12	0.68	1.35	2.32	3.43	4.76	6.46	8.84	11.4	14.9	18.7	21.3	23.3	26.1	29.8	31.5	30.8
-20	0.00	0.00	0.21	0.86	1.74	3.00	4.52	6.66	9.66	13.4	19.2	25.6	30.6	37.4	44.7	47.9	49.4	50.0	49.5
-10	0.00	0.00	0.27	1.00	2.08	3.56	5.53	8.39	12.6	18.4	27.3	34.7	42.3	50.4	53.5	56.4	57.6	58.1	57.4
0	0.00	0.00	0.30	1.07	2.26	3.91	6.18	9.57	14.5	22.0	32.7	41.1	49.0	55.2	57.5	59.5	61.2	62.1	61.9
10	0.00	0.00	0.30	1.07	2.23	3.84	5.99	9.13	13.8	20.5	31.0	40.4	48.3	55.8	58.1	61.1	62.9	64.3	65.5
20	0.00	0.01	0.25	1.00	2.02	3.50	5.34	7.95	11.7	16.7	24.8	34.5	43.1	50.5	57.1	59.5	60.7	62.2	63.4
30	0.00	0.01	0.18	0.86	1.71	2.95	4.46	6.32	8.82	12.4	16.8	23.2	31.2	38.6	45.3	50.8	54.9	58.0	59.8
40	0.00	0.01	0.10	0.63	1.33	2.24	3.42	4.75	6.29	8.23	10.6	13.7	17.0	21.1	25.8	30.0	33.3	35.5	36.5
50	0.00	0.01	0.06	0.38	0.92	1.58	2.33	3.28	4.27	5.33	6.49	7.76	9.05	10.5	12.0	13.4	14.4	15.1	15.3
60	0.00	0.01	0.05	0.15	0.48	0.92	1.41	1.97	2.56	3.22	3.88	4.51	5.14	5.69	6.20	6.63	6.98	7.21	7.33
70	0.00	0.01	0.03	0.08	0.16	0.34	0.62	0.92	1.25	1.58	1.92	2.26	2.58	2.88	3.16	3.41	3.62	3.79	3.91
80	0.00	0.00	0.02	0.04	0.07	0.11	0.17	0.24	0.31	0.40	0.52	0.64	0.78	0.90	1.02	1.13	1.23	1.31	1.38
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.03	0.04	0.05	0.05	0.04	0.02	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.05	0.08	0.10	0.11	0.16	0.17	0.17	0.15
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.06	0.10	0.14	0.18	0.22	0.25	0.29	0.32	0.29
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.07	0.11	0.17	0.24	0.28	0.35	0.41	0.45	0.45

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-13

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.06V I:0.2564A P:1.897W PF:0.6133 Freq:59.97Hz Lamp Flux:94.6795x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Copper Wall Light	WEIGHT:
SPEC.:2.5W 3000K Transparent lattice glass	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.46	0.44	0.42	0.32	0.30	0.28	0.19	0.14	0.12	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-170	0.45	0.45	0.40	0.34	0.32	0.29	0.20	0.16	0.12	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-160	0.41	0.39	0.37	0.35	0.30	0.23	0.18	0.15	0.05	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-150	0.35	0.34	0.31	0.27	0.23	0.19	0.16	0.06	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-140	0.25	0.24	0.22	0.19	0.16	0.09	0.04	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-130	0.10	0.09	0.07	0.05	0.03	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.02	0.04	0.05	0.06	0.06	0.06	0.04	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-70	0.12	0.24	0.34	0.42	0.48	0.51	0.52	0.50	0.46	0.40	0.32	0.22	0.09	0.00	0.00	0.00	0.00	0.00	
-60	0.35	0.68	0.96	1.18	1.34	1.41	1.42	1.36	1.23	1.07	0.88	0.68	0.47	0.26	0.03	0.00	0.00	0.00	
-50	2.17	2.79	3.18	3.34	3.30	3.17	3.07	2.82	2.50	2.14	1.73	1.31	0.92	0.57	0.26	0.00	0.00	0.00	
-40	8.21	9.31	9.73	9.60	9.01	8.05	6.76	5.48	4.53	3.65	2.86	2.15	1.48	0.92	0.47	0.05	0.00	0.00	
-30	31.3	29.4	25.4	22.0	19.5	16.5	13.4	10.6	7.75	5.76	4.29	3.10	2.11	1.30	0.66	0.16	0.00	0.00	
-20	50.1	49.5	47.1	43.0	36.4	28.5	22.8	17.0	12.4	8.43	5.96	4.08	2.72	1.64	0.85	0.26	0.00	0.00	
-10	58.1	58.0	56.4	53.6	48.1	40.9	31.8	23.7	16.8	11.3	7.45	4.99	3.24	1.92	0.98	0.32	0.00	0.00	
0	62.5	61.1	60.0	57.9	53.1	46.6	37.9	28.7	19.6	13.3	8.47	5.57	3.55	2.08	1.04	0.34	0.00	0.00	
10	64.3	63.2	61.1	58.2	53.4	46.9	37.5	27.4	18.9	12.6	8.19	5.44	3.52	2.07	1.05	0.35	0.00	0.00	
20	62.3	60.8	58.7	55.4	49.4	41.0	31.7	22.6	15.8	10.5	7.25	4.90	3.22	1.92	0.99	0.31	0.01	0.00	
30	57.7	54.5	50.0	44.0	36.8	28.9	21.7	16.0	11.3	8.12	5.85	4.12	2.75	1.66	0.84	0.23	0.01	0.00	
40	35.2	32.6	29.0	24.8	20.4	16.4	12.9	9.88	7.70	5.90	4.43	3.20	2.14	1.30	0.65	0.12	0.01	0.00	
50	15.0	14.2	13.0	11.6	10.1	8.66	7.39	6.18	5.07	4.06	3.11	2.25	1.52	0.91	0.42	0.06	0.01	0.00	
60	7.17	6.90	6.53	6.07	5.55	4.98	4.37	3.74	3.10	2.49	1.92	1.40	0.93	0.52	0.16	0.05	0.01	0.00	
70	3.77	3.60	3.38	3.13	2.86	2.56	2.23	1.90	1.58	1.24	0.94	0.65	0.37	0.16	0.08	0.03	0.01	0.00	
80	1.31	1.23	1.14	1.03	0.92	0.79	0.66	0.53	0.40	0.31	0.24	0.17	0.11	0.07	0.04	0.02	0.00	0.00	
90	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
140	0.01	0.02	0.04	0.04	0.05	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
150	0.03	0.06	0.07	0.07	0.07	0.08	0.08	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
160	0.17	0.19	0.19	0.17	0.16	0.12	0.10	0.10	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
170	0.33	0.32	0.28	0.26	0.24	0.22	0.15	0.12	0.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
180	0.46	0.44	0.42	0.32	0.30	0.28	0.19	0.14	0.12	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

H(β) Range:-90 - 90DEGH(β) Interval: 0.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:ADMIN

Test Date:2023-10-13

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352

Humidity:65.0%

Test Distance:13.563m [K=1.0000]

Remarks: