

Project Name:

Fixture Type:

Date:

Completed #:

E.G. Completed Order #:

Aluminum ADJ Beam Deco Path

Area, Integrated Modular Variable, Aluminum, 18" Riser with Module/ADJ Beam Spread, Available in Multiple Variations, 10-15V




FINISHES



SPECIFICATIONS

Electrical / Power: 4W / 5.2 VA / 10-15V	Weight: 2.42 lb
Construction / Body: Aluminum	Dimming: 25%-100%
Lens / Gaskets:	Ambient Operating Temperature: -4°F- 122°F (-20°C-50°C)
Wiring: 6' Lead Wire	Control: Primary (MLV)
LED Life: 50,000 Hrs	Warranty: Housing Warranty: 10 Years; Finish Warranty: 5 Years; LED Warranty: 10 Years
Installation Requirements: Remote low voltage power supply/transformer required	LED Engine: Lumens: 69 / CRI: 80+



* Product specifications, materials, and availability may change without notice. Actual fixtures may vary from the information shown.

Project Name:

Fixture Type:


Date:

Completed #:

E.G. Completed Order #:

Aluminum ADJ Beam Deco Path

Product Line Drawings



Standard Included Accessories



1/2" Threaded 8" Stake
with ADJ Collar

* Product specifications, materials, and availability may change without notice. Actual fixtures may vary from the information shown.

Project Name:

Fixture Type:

Date:

Completed #:

E.G. Completed Order #:

Ordering Guide Continued

Instructions: Steps 7-10 continue on the following pages. Please complete the full ordering guide.

06 Top Accessories		Finish
	ADCO-CAP-039 Deco Path Triangular Hat	
	ADCO-CAP-037 Deco Path Bubble Hat	BK Black
		BZ Bronze
	ADCO-CAP-040 Deco Path Flat Top Dome Hat	

* Product specifications, materials, and availability may change without notice. Actual fixtures may vary from the information shown.

Project Name:

Fixture Type:

Date:

Completed #:

E.G. Completed Order #:

Ordering Guide Continued

Instructions: Steps 8-10 continue on the following pages. Please complete the full ordering guide.

07 Mounts

	SSSD-STK-12-002 1/2" Threaded 12" Trident Stake with 5" Plate		PSD-STK-15-005 1/2" Threaded 15" Commercial Stake
	SSSD-STK-6-007 1/2" Threaded 6" Trident Stake with 3" Plate		SSSD-STK-6-003 1/2" Threaded 6" Mini Stake
	SSSD-STK-6-002 1/2" Threaded 6" Trident Stake with 5" Plate		PSD-STK-12-001 1/2" Threaded 12" Stake
	ASD-JBX-002-(BK/BZ) 1/2" Threaded J-Box		ASD-MNT-001-(BK/BZ) 1/2" Threaded Base

* Product specifications, materials, and availability may change without notice. Actual fixtures may vary from the information shown.

Project Name:

Fixture Type:

Date:

Completed #:

E.G. Completed Order #:

Ordering Guide Continued

Instructions: Steps 9-10 continue on the following pages. Please complete the full ordering guide.

08 Secondary Mounts

ASD-STM-4-020-(BK/BZ) 1/2" Threaded 4" Riser		ASD-STM-ADJ-008-(BK/BZ) 1/2" Threaded ADJ 16-25" Riser
ASD-STM-24-007-(BK/BZ) 1/2" Threaded 24" Riser		ASD-STM-16-006-(BK/BZ) 1/2" Threaded 16" Riser
	ASD-STM-8-005-(BK/BZ) 1/2" Threaded 8" Riser	

* Product specifications, materials, and availability may change without notice. Actual fixtures may vary from the information shown.

Project Name:

Fixture Type:

Date:


Completed #:

E.G. Completed Order #:


Performance Characteristics & Beam Spread Charts

Input Power	4W
Color Temperature (CCT)	30K
Color Rendering Index (Ra)	80+
Beam Angle	60
Max. Candlepower	74.2 cd
Delivered Lumens	71 lm
Efficacy	18.8 lm/W

POLAR GRAPH - INTENSITY



CONE OF LIGHT - ILLUMINANCE



* Product specifications, materials, and availability may change without notice. Actual fixtures may vary from the information shown.

